

NYS TOW TRUCK ENDORSEMENT PRACTICE TEST 4 ANSWERED

Which of the following should you NOT do while unloading a vehicle from a car carrier?

- a. Park the car carrier in a position that is level
- B. Leave adequate space at the rear when parking
- C. Position wheel chocks on the sides of the rear wheels of the car carrier
- D. Tilt the bed so the loaded vehicle is on a slight incline

CORRECT ANSWER C

Where should you not stand when the bed is in a loaded tilted position?

- A. In front of the bed
- B. Behind the bed
- C. The right side of the bed
- D. The left side of the bed

CORRECT ANSWER B

What is a headboard?

- A. A strong and temporary horizontal device affixed between the cab and the load to protect the cab and its occupants
- B. A fragile and permanent vertical device affixed between the cab and the load used to secure the load's positioning
- C. A strong and permanent vertical device affixed between the cab and the load to protect the cab and its occupants
- D. A strong and permanent horizontal device affixed between the cab and the load used to secure the load's positioning

CORRECT ANSWER C

How should you proceed when driving on uneven ground? (Railroad tracks, driveways, speed bumps, dips, speed bumps, potholes, etc.)

- A. Slowly
- B. Brake frequently
- C. Drive quickly to get past the area
- D. Stay to the left

CORRECT ANSWER A

What is the wheel chock?

- A. A device used for towing vehicles by lifting one end of the towed vehicle from under the axle or structural member
- B. A device usually triangular in shape placed in front of the wheel to prevent the vehicle from rolling
- C. Devices used to tie down the wheel of the towed vehicle
- D. A device that attaches to the lift bar for engaging the tires of a towed vehicle